

27-Port Gigabit Uplink 10/100M 24-Port PoE Switch



www.hruiotech.com



Gigabit Uplink 24-port PoE switch, using high-quality high-speed network IC and the most stable PoE chip, The PoE port meets the 802.3af or 802.3at standard. This series of PoE switches can provide seamless connection for 10/100M Ethernet, and the PoE power supply port can automatically detect and supply power to powered devices that comply with IEEE802.3af or IEEE802.3at standards, and non-PoE devices intelligently detect no power supply, only data is transferred.

Main Features

- 24*10/100M POE ports + 2* 1000M Ethernet Uplink ports +1*1000M SFP Port
- Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z standards
- Ethernet port 10/100M rate auto adaptive
- Flow control mode: full-duplex adopts IEEE 802.3x standard, half-duplex adopts Back pressure standard
- Support Port Auto-flip (Auto MDI/MDIX)
- Panel indicators to monitor working status and help fault analysis
- One-key smart switch, supports VLAN, OFF, Extend
- Compatible with 1 U rack installation

Application Environment

Metro Optical Broadband Network:

Data network operators such as telecommunications, cable TV, and network system integration, etc.

Broadband private network:

Suitable for financial, government, oil, railway, electric power, public security, transportation, education and other industries

Multimedia transmission:

Integrated transmission of images, voice and data, suitable for remote teaching, conference TV, videophone and other applications

Real-time monitoring:

Simultaneous transmission of real-time control signals, images and data

Specifications	
I/O Interface	
Power	Input: AC 100-240V, 50/60Hz
Ethernet	24 Port 10/100M PoE + 2 Port 1000M Ethernet Uplink+1 Port 1000M SFP
Performance	
Power Budget	52V 7.69A 400Watt
Switching Capacity	10.8 Gbps
Forwarding Rate	8.035Mpps
Packet Buffer	1.5Mb
MAC Address	2K
Jumbo Frame	9216bytes
MTBF	100000 hours
Standard	
Network protocol	IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab,IEEE802.3ab
PoE Protocol	IEEE802.3af (15.4W) IEEE802.3at (30W)
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A EMS: EN61000-4-2 (ESD)、 EN61000-4-4 (EFT)、 EN61000-4-5 (Surge)
Network Medium	10BASE-T: Cat 3、 4、 5 UTP(≤100 meter) 100BASE-TX: Cat5 or more UTP (≤100 meter) 1000Base-TX : Cat5 or more UTP/STP(≤100 meter)
Optical Media	Multimode fiber : 50/125、 62.5/125、 100/140um Single mode fiber : 8/125、 8.7/125、 9/125、 10/125um
Protection	
Certificate	CE、 FCC、 RoHS

Environment	
Environment	Working Temperature: -20~50°C Storage Temperature: -40~85°C Working Humidity : 10%~90%, non-condensing Storage Temperature: 5%~90%, non-condensing Working Height: Maximum 10,000 feet Storage height: Maximum 10,000 feet
Physical Features	
Dimension	Product Dimension (L*W*H): 440*205*44mm Package Dimension (L*W*H): 500*290*85mm N.W: 1.9kg G.W: 2.4kg
Packing Info	Carton MEAS: 520*445*310mm Packing Qty: 5 units Packing Weight: 13KG
Power Voltage	Input Voltage : AC 100-240 V Power supply: 52V7.69A
Package List	Switch 1 pcs, Power cord 1 pcs, User manual 1 pc, Certification 1 pc, Brackets 1 pair
Indicators	
DIP Switch	<p>VLAN : Port isolation mode. In this mode, the PoE ports (1-24) of the switch cannot communicate with each other, and can only communicate with the UP-link port.</p> <p>OFF: Normal mode, all port can communicate with each other, the transmission distance is within 100 meters, the transmission rate is 10M / 100M adaptive;</p> <p>Extend : Link extension mode, 9-24 ports PoE power supply and data transmission distance can be extended to 250 meters, the transmission rate becomes 10M</p>
LEDs	PWR (power supply) , SW (DIP) , 1-27 (Link&Data)

Ordering Info	
HR901-AF-2421GS-400	27-Port Gigabit Uplink 10/100M 24-Port PoE Switch

Product Picture



Application of topology

