

HR-POE013-WP



1*IEEE802.3af/at (PoE) powered port input

3*IEEE802.3af/at (PoE) powered port output

With network and POE relay extension role

With outdoor waterproof function

Product description

POE013-FS is a 100Mbps Ethernet PoE Extender, which provides 1*100 Mbps

IEEE802.3af/at(PoE) powered port input and 3*100 Mbps IEEE802.3af/at(PoE)

powered ports output. The whole power is 30W, and the average output power is

8W per port. It can be applied to outdoor application scenarios.

Product Parameter

Network Standard	IEEE 802.3、IEEE 802.3u、IEEE 802.3x
------------------	------------------------------------

Port	<p>3*10/100Mbps RJ45 power supply port</p> <p>1*10/100Mbps RJ45 receiving port</p>
POE Power	<p>The whole power is 30W</p> <p>Output power of single port is 24W, average output power per port is 8W</p>
POE Connection	<p>POE input receiving wire core: 1/2+、3/6-、4/5+、7/8-</p> <p>POE output power supply core: 1/2+、3/6-</p> <p>100M Transmission</p>
Performance	<p>Store and forward</p> <p>MAC address table 1k</p> <p>Switching capacity 1.6Gbps</p>
Forwarding Rate	<p>10BASE-T:14880PPS/port</p> <p>100BASE-tx: 148800pps/port</p>
Port Function	<p>Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and backpressure for half-duplex mode</p>
Environment	<p>Operating Temperature: -10°C - -55°C</p>

Power	Input: DC44-57V, 30W; Output: DC44-57V, 24W
Weight &Size	55g 95mm×130mm×35mm(L×W×H)